TOPLOADER PRO

This is our spray washing system which is highly efficient and includes a lot of standard options. Its very user-friendly and can be operated by crane.

The PRO model is our highly efficient spray washing system with toploading. It is manufactured of high quality materials and is popular for many applications such as: Parts after machining, workshops, tools cleaning, maintenance, robot cells etc.

Available modules:

- Spray washing
- Spray rinsing
- · Hot air drying.

Available options

- Filtration system
- Automatic water filling
- Automatic chemical dosing
- Extraction fan
- Stainless steel baskets and fixtures
- Digital control panel.



MODEL	AT 750 PRO	AT 900 PRO	AT 1150 PRO
Volume	150 L	250 L	400 L
Basket size	Ø750 mm	Ø900 mm	Ø1150 mm
Cleaning height max.	540 mm	540 mm	540 mm
Weight capacity max.	200 kg	200 kg	300 kg
Pump flow	250 l/min	250 l/min	280 l/min
Pump pressure	2.4 - 3.2 bar	2.4 - 3.2 bar	3.0 - 4.5 bar
Heating effect	9000 W	9000 W	9000 W
Temperature	20 - 60 °C	20 - 60 °C	20 - 60 °C
Power supply	32 A	32 A	32 A



√ Level sensor

Used for protection of heating elements and stainless steel pump.

√ CE - European Machine Directive

The spraywasher is produced in accordance with the European Machine Directive.

√ Motordriven rotating basket

The motordriven rotation ensures reliable cleaning results every time regardless of the geometry and size of the parts.

✓ Prepared for extra options

Prepared for oil skimmer, automatic water filling, extraction fan and filtration system.

√ Smart and user-friendly design

Very compact and user-friendly design makes it easy to access and maintain and makes it possible to load bycrane.

√ Adjustable machine feet

Adjustable stainless steel machine feet, and can also be supplied on wheels.

√ User-friendly analog control

Simple and reliable user-interface that makes it easy to operate.

√ Highly efficient spraying system

Produced with a high flow spraying system combining flat-jet nozzles and point nozzles from all angles inside the machine.

✓ Including basket

filter 400 micron.

A stainless steel basket is included, and specially designed baskets are available upon request.

✓ Integrated stainless steel coarse filter Middle-plate including stainless steel coarse